Product Brochure

SatTrooper 2

60 cm Ku- or Ka-Band Auto-Pointing Manpack Terminal

Operational Advantage

Built for fast-moving field operations, the SatTrooper 2/60 cm delivers reliable, mission-critical satellite connectivity in a lightweight, rugged and fully automatic terminal. Its compact manpack design, one-person deployment and rapid automatic acquisition reduce setup time and operator workload, helping teams establish dependable communications wherever the mission takes them.

- **Faster time to network.** One-button automatic acquisition in less than two minutes minimizes setup time and operator workload.
- **Simple one-person deployment.** Tool-less assembly, integrated GPS and software-controlled pointing streamline field operation.
- **Dependable RF performance.** The 60 cm ring-focus architecture delivers high gain and low side-lobe performance in a compact terminal.
- **Network freedom.** OpenAMIP-based control supports Gilat modems and compatible third-party external modems.
- **Continuity under pressure.** Manual control provides an emergency operating mode, while intelligent auto-reacquisition restores pointing after signal loss.
- **Power autonomy.** Optional tactical batteries and a hot-swap junction box support uninterrupted operation during battery replacement.

Mission-Ready by Design

- **Two optimized RF models.** Choose a dedicated Ku-band model for linear polarization or a dedicated Ka-band model for circular polarization. The bands are offered in separate, non-switchable configurations.
- **Flexible acquisition.** Supports DVB-S / DVB-S2X acquisition with an optional beacon receiver, plus OpenAMIP modem-assisted pointing.
- **Precise three-axis control.** Motorized azimuth, elevation and polarization control supports pointing accuracy of 0.2 degrees or better.
- **Compact integration choices.** Deploy with an external modem or select an integrated Gilat modem card for a streamlined all-in-one terminal.
- **Field transport options.** Select a rugged hardcase or an ergonomic tactical backpack according to the mission profile.
- **Broad RF configuration.** F-Type or N-Type RF connectors and a wide range of BUC power options help tailor the terminal to the network design.

From Case to Connectivity

A compact, field-deployable system combining automatic pointing, intelligent control and flexible modem integration.

Mission Applications

- Tactical field communications
- Military and government deployments
- Emergency response
- Rapidly deployable command posts



SatTrooper 2/60 cm
Ku and Ka Band



Manpack



Hardcase

Technical Specifications

Dedicated RF Model Options

RF Parameter	Ku-Band Model	Ka-Band Model
Configuration	Dedicated Ku-band; not band-switchable	Dedicated Ka-band; not band-switchable
Reflector	60 cm	60 cm
Polarization	Linear, motorized	Circular, manual
Tx frequency range	13.75–14.50 GHz	27.5–31.0 GHz
Rx frequency range	10.70–12.75 GHz	17.7–21.2 GHz
Tx gain	36.82 dBi @ 14.15 GHz	43.0 dBi @ 29 GHz
Rx gain	35.93 dBi @ 12.45 GHz	40.3 dBi @ 19.7 GHz

Antenna & Control

Reflector material:
Composite; optional carbon fiber
System weight:
12.7 kg, excluding BUC and modem
Acquisition time:
Less than 2 minutes
Pointing accuracy:
0.2 degrees or better
Azimuth travel: 0°–360° degrees
Elevation travel: 0°–90° degrees
Polarization travel:
0°–180° degrees (Ku-Band)
Mechanical Switch – Circular (Ka-Band)

Tracking & Control

Satellite Acquisition Time :
< 2 minutes (Automatic)
Pointing Accuracy: ≤ 0.2°
ACU Protocols / Modes:
OpenAMIP, DVB-S2 / DVB-S2X receiver, optional Beacon Receiver

Power & Electrical

Consumption:
< 60 W maximum (excluding BUC and modem)
Supply: 100–240 VAC, 50/60 Hz
Field power option:
Optional hot-swappable tactical battery set with continuous power junction box

Environmental & Ruggedness

Operating wind:
40 km/h unanchored; 70 km/h anchored
Operating temperature:
–20° C to +60° C
Storage temperature:
–30° C to +70° C
Ingress protection:
IP66 dust-tight & withstands high-pressure water jets)
Humidity:
0–100% RH, condensing
Mil-STD: MIL-STD810H

Transport

Hardcase:
Rugged hardcase; 73 x 55 x 44 cm
Hardcase total weight: 24 kg

Tactical backpack:
Ergonomic manpack
Military-grade with contoured support and reinforced load carriage. weight 5 kg
Manpack total weight:
17.7 kg, excluding modem, BUC and battery set

Configuration Options

RF connectors:
F-Type or N-Type
Acquisition:
Optional beacon receiver
Ruggedization:
MIL-STD 810H configuration option (Full Compliance)
Modem:
Integrated Gilat modem card or compatible external modem

Note: Ku-band and Ka-band are supplied as separate dedicated SatTrooper 2 models; the operating band is not field-switchable.
Specifications are subject to change without notice.

All registered trademarks are the property of their respective companies. This brochure is being provided for informational purposes only. The details contained in this document, including product and feature specifications, are subject to change without notice and shall not bind Gilat to a specific product or set of features related thereto. DVB is a registered trademark of the DVB Project.

22/10/2026