

SatTrooper 2

60 cm Ku- or Ka-Band Auto-Pointing Manpack Terminal

Operational Advantage

Built for fast-moving field operations, the SatTrooper 2/60 cm delivers reliable, mission-critical satellite connectivity in a lightweight, rugged and fully automatic terminal. Its compact manpack design, one-person deployment and rapid automatic acquisition reduce setup time and operator workload, helping teams establish dependable communications wherever the mission takes them.

- **Faster time to network.** One-button automatic acquisition in less than two minutes minimizes setup time and operator workload.
- **Simple one-person deployment.** Tool-less assembly, integrated GPS and software-controlled pointing streamline field operation.
- **Dependable RF performance.** The 60 cm ring-focus architecture delivers high gain and low side-lobe performance in a compact terminal.
- **Network freedom.** OpenAMIP-based control supports Gilat modems and compatible third-party external modems.
- **Continuity under pressure.** Manual control provides an emergency operating mode, while intelligent auto-reacquisition restores pointing after signal loss.
- **Power autonomy.** Optional tactical batteries and a hot-swap junction box support uninterrupted operation during battery replacement.

Mission Applications

- Tactical field communications
- Military and government deployments
- Emergency response
- Rapidly deployable command posts

Mission-Ready by Design

- **Two optimized RF models.** Choose a dedicated Ku-band model for linear polarization or a dedicated Ka-band model for circular polarization. The bands are offered in separate, non-switchable configurations.
- **Flexible acquisition.** Supports DVB-S / DVB-S2X acquisition with an optional beacon receiver, plus OpenAMIP modem-assisted pointing.
- **Precise three-axis control.** Motorized azimuth, elevation and polarization control supports pointing accuracy of 0.2 degrees or better.
- **Compact integration choices.** Deploy with an external modem or select an integrated Gilat modem card for a streamlined all-in-one terminal.
- **Field transport options.** Select a rugged hardcase or an ergonomic tactical backpack according to the mission profile.
- **Broad RF configuration.** F-Type or N-Type RF connectors and a wide range of BUC power options help tailor the terminal to the network design.

From Case to Connectivity

A compact, field-deployable system combining automatic pointing, intelligent control and flexible modem integration.



SatTrooper 2/60 cm
Ku and Ka Band



Manpack



Hardcase

Technical Specifications

Dedicated RF Model Options

RF Parameter	Ku-Band Model	Ka-Band Model
Configuration	Dedicated Ku-band; not band-switchable	Dedicated Ka-band; not band-switchable
Reflector	60 cm	60 cm
Polarization	Linear, motorized	Circular, manual
Tx frequency range	13.75–14.50 GHz	27.5–31.0 GHz
Rx frequency range	10.70–12.75 GHz	17.7–21.2 GHz
Tx gain	36.82 dBi @ 14.15 GHz	43.0 dBi @ 29 GHz
Rx gain	35.93 dBi @ 12.45 GHz	40.3 dBi @ 19.7 GHz

Antenna & Control

Reflector material:

Composite; optional carbon fiber

System weight:

12.7 kg, excluding BUC and modem

Acquisition time:

Less than 2 minutes

Pointing accuracy:

0.2 degrees or better

Azimuth travel: 0°–360° degrees

Elevation travel: 0°–90° degrees

Polarization travel:

0°–180° degrees (Ku-Band)

Mechanical Switch – Circular

(Ka-Band)

Tracking & Control

Satellite Acquisition Time :

< 2 minutes (Automatic)

Pointing Accuracy: ≤ 0.2°**ACU Protocols / Modes:**

OpenAMIP, DVB-S2 / DVB-S2X receiver, optional Beacon Receiver

Power & Electrical

Consumption:

< 60 W maximum

(excluding BUC and modem)

Supply: 100–240 VAC, 50/60 Hz

Field power option:

Optional hot-swappable tactical

battery set with continuous

power junction box

Environmental & Ruggedness

Operating wind:

40 km/h unanchored; 70 km/h anchored

Operating temperature:

–20° C to +60° C

Storage temperature:

–30° C to +70° C

Ingress protection:

IP66 dust-tight & withstands high-pressure water jets)

Humidity:

0–100% RH, condensing

Mil-STD: MIL-STD810H

Transport

Hardcase:

Rugged hardcase; 73 x 55 x 44 cm

Hardcase total weight: 24 kg

Tactical backpack:

Ergonomic manpack

Military-grade with contoured support and reinforced load carriage. weight 5 kg

Manpack total weight: 17.7 kg, excluding modem, BUC and battery set

Configuration Options

RF connectors:

F-Type or N-Type

Acquisition:

Optional beacon receiver

Ruggedization:

MIL-STD 810H configuration option (Full Compliance)

Modem:

Integrated Gilat modem card or compatible external modem

Note: Ku-band and Ka-band are supplied as separate dedicated SatTrooper 2 models; the operating band is not field-switchable. Specifications are subject to change without notice.