

EnduroStream 500W Ka-Wideband Block Upconverter

WBAM-500G3 / WBAK-500G3

Field-Proven Performance

Wavestream's EnduroStream 500W Ka Wideband Solid State Block Upconverter leads the industry in linear power in this Gateway-Ready Redundant design, ensuring the maximum available power for multiple carrier inputs.

This Wideband BUC covers both Military Ka and Commercial Ka frequency bands.

The Ka Wideband Block Upconverter offers forward power monitoring, 30 dB of hitless step attenuation, dual-Ethernet ports for control interface, and AC input power.

Features

- Designed for Gateway Applications
- Solid State Gallium Arsenide (GaN) Transistor Technology
- Ka-band BUC providing > 200W multicarrier linear power
- Covers Military and All Commercial Ka Frequency Bands
- Built-In Redundancy
 - 1:1 Redundancy for Power Supplies
 - 1:1 Redundancy for Block Up Converters
- Ruggedized package with Hot Swappable Modules
- Automatically Aligns Gain and Phase of the RF Modules utilizing WaveAlign™ Technology

Wavestream Advantages

What sets Wavestream products apart from traditional amplifier solutions is the innovative Spatial advantEdge™ technology. This unique patented technology allows for generation of higher output power in more efficient, and more compact product packages that are more reliable.

Wavestream products are optimized for Linear operation, drawing less power when backed off to help save valuable energy resources. They generate less heat, and have superior heat sinking ensuring a higher Mean Time Between Failures (MTBF) for greater reliability and lower lifecycle maintenance costs.

Benefits

- All Solid State GaN Amplifier Designed With Graceful Degredation
- Built-in Full Redundancy For Power Supply and Upconverter
- Hot Swappable Modules with WaveAlign™ Technology for Automatic Alignment
- High Reliability Design, Always-On Solution Ensures Minimal Downtime and High Availability
- Low Cost of Ownership



(Shown with optional rack)

Technical Specifications

RF Specifications

Transmit Frequency:

30.0 – 31.0 GHz (Option 1)
27.5 GHz – 31.0 GHz (Option 2)
(Custom frequency plans available)

IF Frequency Bands:

1000 – 2000 MHz (Option 1)
950 – 1950 MHz (Option 2)

LO Frequency:

29.0 GHz (Option 1)
26.55 GHz, 27.3 GHz, 28.0 GHz,
29.0 GHz (Option 2)

Reference Frequency:

10 MHz on a dedicated connector

Small Signal Gain:

70 dB \pm 1.5dB (Nominal)

Gain Adjustment:

30 dB in 0.25 dB linear steps
(nominal)

Gain Variation:

- Over full band at fixed temp:
<4 dB
- Over temp and fixed frequency:
4 dB p-p over operating range

Peak Envelope Power:

57 dBm (500W) (Nominal)

Linear Output Power:

53 dBm (200W)

- **Intermodulation** (Third order intermodulation product relative to combined power of two carriers at Output Power): -25dBc

- **Spectral Regrowth** (OQPSK at 1.0x offset 2Msym/s with a = 0.35): -30dBc

- **AM/PM Conversion** (Output power at which AM-PM conversion reaches 2.0°/dB)

Phase Noise:

- 10 Hz: -35 dBc/Hz
- 100 Hz: -65 dBc/Hz
- 1 kHz: -75 dBc/Hz
- 10 kHz: -85 dBc/Hz
- 100 kHz: -97 dBc/Hz
- 1 MHz: -115 dBc/Hz
- 10 MHz: -120 dBc/Hz

Noise Power Density

-76 dBm/Hz

In Tx Band:
(at Linear Output Power)

All Output Spurious and Products:

< 60 dBc

Physical

Envelope Size:

11U Rack
20.0"L x 19.0"W x 19.16"H
(50.8 x 48.26 x 48.67 cm)

Weight: 325 lbs (147.4 kg)

Operating Temperature (Ambient Air):

-40°C to + 60°C
(-40°F to + 140°F)

Relative Humidity:

Up to 100%

Shock & Vibration:

MIL-STD-810G

Altitude:

10,000 ft above sea level
(operating)

Interfaces

Input Connector:

SMA Female

IF Input Impedance: 50 Ohms

IF Input VSWR: 1.5:1

RF Output Connector:

WR-28

RF Output VSWR:

1.3:1 maximum

AC Connector and M&C Connector:

MIL Circular

M&C Connectivity: Ethernet -

Dual Channel (10/100 MB/s)

M&C Protocol:

SNMP and UDP

Power

AC Power: 189 to 264 VAC

AC Power Draw:

- 2800W (typical) (at Linear Output Power)

- 3600W (typical) (at Peak Envelope Power)

- Power Factor: > 96%

Base Model

WBAM-500G30 (Option 1)

WBAK-500G30 (Option 2)

About Gilat Wavestream

Gilat Wavestream sets the standard in the design and manufacture of next generation high power solid state amplifiers. Wavestream's Family of Ka, Ku and X-band Solid State Power Amplifiers (SSPAs), Block Upconverters (BUCs) and transceivers provide systems integrators with field-proven, high performance solutions designed for ground mobile and fixed, gateway and airborne satellite communication systems worldwide.

These items are subject to the Export Administration Regulations (EAR), 15 C.F.R. Parts 730-774, and may not be exported or transferred to any non-U.S. person, except as authorized by the U. S. Department of Commerce.

Contact Us

545 West Terrace Drive
San Dimas, California 91773 USA
T. +1 909 599 9080
F. +1 909 599 9082

www.wavestream.com
sales@wavestream.com